

Two way stretch top cover with taped
 Infection control seams and side skirts



premium8

One of the best value for feature, full suspension alternating mattress replacement systems on the market. The premium8 has features of acute systems many times the price.

This system still shares many of the quality features of the premium8acute including dual cell press studs as well as a fully sealed top cover with infection control side skirts.

Use only with the consent and supervision of a suitably qualified health professional.

product specification

The analogue control unit allows softer settings on static mode for pressure relief during transport as well as full pressure support for patient handling and transfer.

Quick Facts

- Mattress replacement system
- Care level - Medium Risk
- Analogue control unit with adjustable static settings.
- Elasticized multi-fit top cover
- Adjustable straps to secure to bed frame
- Top cover seam sealing and infection control flaps
- Spring Loaded Anti-kink hoses
- Non slip pads and positioning handles on base
- Static head section with integrated CPR pull

control unit

control interface	analogue
dimensions (WxHxD mm)	290x272x128mm
weight	2.9kg
air output	6.5 litres per minute
hose connection type	quick release connectors
timed static function	✗
alarms	visual
internal power down alarm	✗
fuse rating (Amps)	mains plug - 3A, control unit 1A (x2)
mode of operation	continuous
electrical safety	EN 60601.1:1996, UL2601-1 safe

support surface

support type	mattress replacement
dimensions (LxWxH millimetres)	2000x880x200mm
alternation type	1 in 2
alternation cycle time	12 minutes
base material	TPU coated nylon 420 denier woven fabric
cell material	TPU coated 210 denier nylon fabric
cell in cell technology	✗
side buffer	✓ (optional)
number of cells	21
static head cells	✓
CPR function	pull tag
anti kink hosing	✓
micro air loss feature	✗
positioning handles	✓

top cover

top cover material	PU coated 2 way stretch nylon
attachment type	quick release zipper
Infection control side skirts	✓
seam joining	tape sealed

general

risk category	high risk
maximum user weight guide	180kg
carry bag included	✓