

Infection control seams and skirts



Hinged base to contour to bed frame

Easy to operate digital interface

CPR handle for rapid deflate

Heel

Supportive side bolsters

Use only with the consent and supervision of a suitably qualified health professional.

premium9digital

The latest generation to our premium range, the premium9digital alternating mattress replacement system incorporates over ten years of experience in pressure care. The premium9digital is designed for patients at high risk or with pressure ulcers or sensitive skin and tissue.

With a range of unique features, the premium9digital mattress replacement system raises the benchmark in value for feature rich pressure care solutions for the acute care environment.

The premium9digital offers enhanced cell in cell technology to deliver a safety mattress that offers true peace of mind.

product specification

Permanent side bolsters aid in lateral stability while enhancing the effectiveness of the 1 in 3 alternation cycle in the main lateral cells.

The cells are designed to give an individualized therapy depending on whether they support the heel, sacral or upper body areas.

The digital control unit is light, quiet, vibration free and extremely intuitive to set-up and operate.

Non-continuous operation doubles the life of the compressor.

Quick Facts

- Mattress replacement with side bolsters
- Very high risk care level
- For therapy and prevention
- Digital control unit with non-continuous operation
- Rapid release CPR handle for fast deflate. A transport cap allows patient suspension for up to 30 hours
- Static head cell section
- Integrated cell in cell safety mattress
- Unique hinged base to conform to bed movement
- Specially designed heel zone

control unit

control interface	digital
dimensions (WxHxD)	290x272x128mm
weight	2.9kg
air output	6.5 litres per minute
hose connection type	rapid release handle
timed static function	✓
alarms	audible/visual
internal power down alarm	✓
fuse rating (Amps)	mains plug - 3A, control unit 1A (x2)
mode of operation	non-continuous
electrical safety	CE, UL

support surface

support type	mattress replacement
dimensions (LxWxH)	1970x900x250mm
alternation type	1 in 3
alternation cycle time	12 minutes
base material	PU coated nylon 420 denier woven fabric
cell material	TPU coated 210 denier nylon fabric
cell in cell technology	✓
side buffer	✓ (integrated)
number of cells	19
static head cells	✓
CPR function	rapid release handle
anti kink hosing	✓
micro air loss feature	✗
positioning handles	✓

top cover

top cover material	PU coated 2 way stretch nylon
attachment type	quick release zipper
Infection control side skirts	✓
seam joining	tape sealed

general

risk category	very high risk
maximum user weight guide	180kg
carry bag included	✓